



Revision Date: 31.03.2025

Technical Data Sheet

Product	High Gloss Enamel
Product Code	EN
Description	A high quality paint suitable for interior and exterior use on wood, plaster or steel surfaces as a protective and decorative coat.
Composition	Alkyd Base

Physical Properties

Colour	Colour card, black and white
Appearance	High gloss
Viscosity	72 KU
Shelf Life	Approximately 12 months
Storage Conditions	Normal
Pack Size	1ℓ, 5ℓ, 20ℓ and 200ℓ

Application Properties

Method	Brush or roller
Theoretical Coverage (m² / ℓ)	6 - 8
Recommended No of Coats	Two
Drying time at 25°C	4 hours (touch dry) 8 hours (hard dry)
Overcoating time at 25°C	12 hours
Thinning	Up to 5% with Turpentine if necessary
Cleaning solvent	Turpentine
Recommended System	As a finishing coat on suitably prepared and primed surfaces. For interior and exterior application. Prime with pigmented plaster primer or universal undercoat.

Precaution

Flashpoint	Above 30°C
Toxicity	Normal when used in well ventilated areas

Note

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.