



Revision Date: 11.06.2024

Technical Data Sheet

Product	WATER BASED ROADLINE PAINT
Product Code	RLW
Description	A marking paint for use on all road surfaces or demarcation lines in factories or warehouses, ideal for spraying. UV resistant and quick drying. Hard wearing and scratch resistant.
Composition	WATER BASED EMULSION

Physical Properties

Colour	White / Yellow / Black / Red
Appearance	Satin
Viscosity	77-80 KU
Shelf Life	6 months
Storage Conditions	Normal
Pack Size	5ℓ, 20ℓ and 200ℓ

Application Properties

Method	Brush, roller or airless spray
Volume Solids (Typical)	70%
Recommended Average DFT in microns	150 min
Theoretical Coverage (m² / ℓ)	3 at 150 microns DFT
Wet Film Thickness in microns	200 microns
Recommended No of Coats	one
Drying Time at 25°C	30 minutes (touch dry) 60 minutes (hard dry) WEATHER DEPENDENT
Overcoating Time at 25°C	60 minutes
Thinning	ready for use, thinning not recommended
Cleaning Solvent	WATER
Recommended System	For use on clean concrete or asphalt surfaces Glass beads compulsory

Precaution

Flashpoint	N/A
Toxicity	Non Toxic

Note

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.