



Revision Date: 31.03.2025

Technical Data Sheet

Product	Eggshell Enamel
Product Code	EE
Description	A high quality paint for interior use only, can be used on surface areas that come into contact with steam and soiling. I.e Bathrooms and Kitchens. A hard-wearing finish for doors and trims.
Composition	Alkyd Base
Features and Benefits	Mar and scratch resistance. High hiding properties and washable.

Physical Properties

Colour	White, ivory, cream and light grey
Appearance	Semi-gloss
Viscosity	72 KU
Shelf Life	Approximately 12 months
Storage Conditions	Normal
Pack Size	5ℓ, 20ℓ and 200ℓ

Application Properties

Method	Brush or roller
Theoretical Coverage (m² / ℓ)	6 - 8
Recommended No of Coats	Two
Drying time at 25°C	4 hours (touch dry) 16 hours (hard dry)
Overcoating time at 25°C	Overnight
Thinning	up to 5% with Turpentine if necessary
Cleaning solvent	Turpentine
Recommended System	As a finishing coat on suitably prepared and primed interior surfaces. Prime with pigmented plaster primer or universal undercoat

Precaution

Flashpoint	Above 32°C
Toxicity	Normal when used in well ventilated areas

Note

No guarantee is implied by the recommendations contained herein since the data sheet is issued for information purposes only. Method of application on surface, cleanliness and conditions of use etc. are beyond our control.